

HUMIDITY TRANSMITTERS RHT Series

Wall mount relative humidity transmitters for building automation systems



RHT relative humidity transmitters are engineered for building automation systems in the HVAC/R industry. The RHT measures relative humidity (rH), and temperature (T). RHT devices are available with large touchscreen display making configuration of the device quick and easy.

RHT series devices include:

- Separate field configurable output for each measurement parameter (rH, T).
- Proportional output options including: voltage (0–10 V, 2–10 V) and current (4–20 mA).

RHT series device options offer:

- 2" x 3" touchscreen display
- Field configurable relay for any of the two parameters
- Modbus configuration



The versatility of the RHT series air quality transmitters ensures that the right product for your application is available.

APPLICATIONS

RHT series devices are commonly used to monitor:

- humidity and temperature levels in offices, public spaces, hospitals, meeting rooms and classrooms
- humidity and temperature in various commercial applications
- humidity and temperature in HVAC/R environment

MODEL SUMMARY

Description	RHT	
	Model	Product code
Relative humidity transmitter for room	RHT	301.002.001
- with display	RHT-D	301.002.002
- with relay and display	RHT-1R-D	301.002.004
- with Modbus configuration and display	RHT-MOD-D	301.002.003
- with Modbus configuration, relay and display	RHT-MOD-1R-D	301.002.005

HUMIDITY TRANSMITTERS

RHT Series

SPECIFICATIONS

Performance

Measurement ranges:

Temperature: 0...50 °C

Relative humidity: 0–90 %

Accuracy:

Temperature: <0.5 °C

Relative humidity:

±4 % max @0...50 °C and 0–90 % rH

Total error band includes accuracy, hysteresis and

temperature effect over 5...50 °C and

10–90% rH.

Technical Specifications

Media compatibility:

Dry air or non-aggressive gases

Measuring units:

°C and % rH

Measuring element:

Temperature: Pt1000

Relative humidity:

Thermoset polymer capacitive sensing element

Environment:

Operating temperature: 0...50 °C

Storage temperature: -20...70 °C

Humidity: 0 to 95 % rH, non condensing

Physical

Dimensions:

Case: 99 x 90 x 32 mm

Weight:

150 g

Mounting:

3 screw holes slotted, 3.8 mm

Materials:

Case: ABS

Protection standard:

IP20

Display (Optional)

Touchscreen

Size: 77.4 x 52.4 mm

Electrical connections:

Power supply:

5-screw terminal block

(24 V, GND, rH, T, NC)

12–24 AWG (0.2–1.5 mm²)

Relay out:

3-screw terminal block

(NC, COM, NO)

12–24 AWG (0.2–1.5 mm²)

Electrical

Input:

24 VAC or VDC, ±10 %

Current consumption: max 90 mA (at 24 V) +

10 mA for each voltage output or 20 mA for

each current output

Temperature output signal:

0–10 V, R>1 kΩ

2–10V, R>1 kΩ

4–20 mA, R<500 Ω

Relative humidity output signal:

0–10 V, R>1 kΩ

2–10 V, R>1 kΩ

4–20 mA, R<500 Ω

Relay out:

SPDT Relay, 250 VAC / 30 VDC / 6 A

Conformance

Meets requirements for CE marking:

EMC Directive: 2014/30/EU

RoHS Directive: 2002/95/EC

WEEE Directive: 2012/19/EU



How to generate a model?

Example: RHT-1R-D	Product Series			
	RHT	Relative humidity transmitter, analog configurations		
RHT-MOD	Relative humidity transmitter, Modbus configuration			
	Mounting			
		Wall mount		
	Duct	Duct mount (not available with relay)		
		Relay		
	-1R	With relay		
		Without relay		
		Display		
	-D	With Display		
		Without Display		
Model	RHT	-1R	-D	